

OK Tigrod NiCrMo-3

Bare corrosion and heat-resisting Ni-Cr-Mo rods for welding of high alloyed heat-resisting and corrosion resisting materials, 9%Ni-steels and similar steels with high notch toughness at low temperatures. Also for joining of dissimilar metals of the types mentioned. The weld metal has very good mechanical properties at high and low temperatures. Good resistance to pitting and stress corrosion.

Classifications Wire Electrode	SFA/AWS A5.14: ERNiCrMo-3 EN ISO 18274: S Ni 6625
Approvals	CE EN 13749 DNV-GL VL 1.5Ni up to VL 9Ni NAKS/HAKC 2.0-2.4 mm VdTÜV 12460

Approvals are based on factory location. Please contact ESAB for more information.

Alloy Type	Alloyed nickel (Ni + 22 % Cr + 9 % Mo - 3.5 % Nb)
, moy Typo	7 110 300 1110 101 (111 1 22 70 01 1 0 70 1110 0 0.0 70 110)

Typical Tensile Properties	vical Tensile Properties				
Condition	Yield Strength	Tensile Strength	Elongation		
As Welded	550 MPa (80 ksi)	780 MPa (113 ksi)	40 %		

Typical Charpy V-Notch Properties	pical Charpy V-Notch Properties				
Condition	Testing Temperature	Impact Value			
As Welded	-196 °C (-321 °F)	100 J (74 ft-lb)			

Typical Wire Composition %							
С	Mn	Si	Ni	Cr	Мо	Fe	Nb+Ta
0.02	0.04	0.06	bal	22.7	8.6	0.3	3.5